

NMC-RJ88RZ50UD1-PT-100



RJ45/8P8C, Three prongs pin (Universal), Cat.5e, 50U, UTP, round type, allow wires to pass-through

Registered Jack (RJ) Plugs are designed as standardized interface for termination of solid and stranded (patch cord) cables in the production of patch cords, for connecting cameras and some other networking equipment.

To increase the maximum number of reconnections, general life and the protection of copper contacts connectors from oxidation, they are additionally coated with gold plating.

NMC-RJ88RZ50xx1-PT-100 are designed to allow wires pass through the connector ensuring that all wires are in right order for termination.

Ordering Table

| P/N | Type / Category | Individual Packing | | | Transport packaging | | |
|---------------------------|-----------------|--------------------|----------------|------------|---------------------|----------------|------------|
| | | Quantity | Dimensions, mm | Weight, kg | Quantity | Dimensions, mm | Weight, kg |
| NMC-RJ88RZ50UUTP / Cat.5e | | 100 pcs | - | - | 40 packs | 350x250x240 | - |

NMC-RJ88RZ50UD1-PT-100

RJ45/8P8C, Three prongs pin (Universal), Cat.5e, 50U, UTP, round type, allow wires to pass-through

Detailed characteristics

| Characteristic | Value |
|---------------------------------|---|
| Connector type | RJ45/8P8C |
| Category | 5e |
| Bandwidth, MHz | 100 |
| Conection style | Unshielded |
| Material of contacts | Phosphor bronze |
| Contact plating | Gold, 50 micro-inches |
| Knife type | Universal |
| Diameter of conductors, AWG | 24-26 (0.51-0.40 mm) |
| Housing material | Transparent polycarbonate, meets UL 94-V2 |
| Temperature ranges | Storage from -40 to +70°C. Installation is from -10 to +50°C. Operation from -30 to +80°C |
| Number of ports for main cables | 1 year |
| Packaging | Polyethylene bag (100 pcs) |