

NMF-PL86X86-1PASCD-WT



British type wall-mounted fiber optic faceplate, angled port, for SC Duplex / LC Quadro adapter, white

NIKOMAX Fiber optic faceplate, angled port design applied in work area with standard size 86×86 and compatible with full series NIKOMAX fiber optic adapter.

Ordering Table

P/N	Individual package		Group package		Freight package			
	Volume, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg	Quantity	Dimensions, mm	Weight, kg
NMF-PL86X86-1114x114x1.5	-	-	50 pcs.	300x280x110	-	400 pcs.	570x310x460	-

NMF-PL86X86-1PASCD-WT

British type wall-mounted fiber optic faceplate, angled port, for SC Duplex / LC Quadro adapter, white

Detailed characteristics

Characteristic	Value
Type of installed modules	Fiber adapter
Dimensions (on the front side, WxHxD), mm	86 x 86 x 14.7
Plastic material	Meets UL94V-0 ABS
Installation	Wall-mounted
Temperature range	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C
Color	White
Number of ports for main cables	1 year
Packaging	Individual - plastic bag
Adapter type / Polishing	SC duplex / LC quadro