


NMF-PT1S2C0-SCU-xxx-001-2





Fiber optic patch cords (pigtail) are designed to connect fiber optical cable to active network switches and patch panels by fusion splicing.

Fiber optic pigtails are manufactured with either multimode or single-mode fibre and terminated only on one side by SC, LC, FC, ST connector type and polished UPC or APC in a diameter of 0.9 mm and tight buffered outer jacket.

Single-mode pigtails have an outer protective jacket in yellow color, and multimode pigments are in orange color.

Ordering Table

P/N	Connector type	Polishing	Length, м	Individual packing Volume, м3	Weight, kg
NMF-PT1S2C0-SCU-X>	(XSC	UPC	1	0.000225	0.011



NMF-PT1S2C0-SCU-xxx-001-2

Fiber Optic Patch Cord (Pigtail), SM 9/125, SC/UPC-Empty, LSZH

Detailed characteristics

Characteristic	Value			
Outer jacket material	LSZH			
Temperature ranges	Storage from -20 to +65 ° C. Operation -20 to +65 ° C			
Warranty	1 year			
Packaging	Plastic bag			
Type of optical fiber	Single mode 9/125			
Class of fiber	OS2 / G.652.D			
Type of cable	Patch Cord (Pigtail)			
Connectors / Polishing	SC/UPC			
Diameter of outer jacket, mm	0.9			
Color of outer jacket	Yellow			
Insertion loss	≤ 0.3 dB			
Return loss	≥ 50 dB			